

AFTERSHOCK™

FUNGICIDAL COATING

DESCRIPTION

Product No.: 8390 White

AfterShock is an EPA-registered antimicrobial coating designed to kill residual mold and mildew remaining after precleaning contaminated surfaces. AfterShock also inhibits the future growth and spread of mold and mildew on the cured film surface in residential and institutional buildings. This extremely durable, easy to apply, 100% acrylic sealant offers the ultimate in durability in combination with excellent fungicidal characteristics to address mold growth from water damage. AfterShock is recommended for use on interior wall surfaces such as plaster, wallboard, drywall, concrete, masonry block, wood, primed metal and galvanized metal. AfterShock is also recommended for use on interior wood framing, primed metal, concrete, and wallboard inside the wall cavity. Do not use for HVAC system applications.

PROPERTIES

- EPA Reg. No.: 73884-1
- EPA Est. No.: 73884-MA-1
- Solids:
 - 41.96% ± 2 by weight
 - 32.73% ± 2 by volume
- Viscosity at 70°F: 95 ± 5 Krebs Units
- Specific Gravity @ 20°C: 1.18
- Flash Point: Noncombustible
- Odor: Virtually odorless
- Shelf Life: @ 70°F, 36 months min.
(original sealed containers)
- Finish: 60° Gloss @ 60 ± 5°
- Coverage:
 - Smooth surfaces: 250-400 ft²/gal
 - Porous Surfaces: 150-300 ft²/gal
 - Spray- 50% of above
- Dry Time @ 70°F:
 - To touch: 1 hour
 - To recoat: 4 hours
- Packaged: 5 gallon containers

SURFACE PREPARATION

CHECK WITH ALL LOCAL, STATE, AND FEDERAL REGULATIONS BEFORE BEGINNING WORK OR USING THIS PRODUCT. FIX THE SOURCE OF ANY MOISTURE PROBLEMS PRIOR TO REMEDIATION. DO NOT ATTEMPT TO SALVAGE DAMAGED OR STRUCTURALLY UNSOUND BUILDING MATERIALS. CONSULT WITH A QUALIFIED PROFESSIONAL TO PERFORM A THOROUGH INSPECTION AND SUPPLY WORK SPECIFICATIONS APPROPRIATE TO THE PROJECT.

AfterShock is supplied ready to use. Stir thoroughly. Do not mix with other coatings, solvents or colors in oil. Remove damaged materials and clean surfaces. Surface must be free of dust, mildew, mold, dirt, grease, loose paint, oil, glue size, calcimine, wax, soap and other surface contamination. Patch surface irregularities with an appropriate patching compound. AfterShock is self-priming over bare gypsum drywall, composition board, ceiling tile and concrete. Do not apply when air or surface temperature is below 50°F or when drying conditions are poor. Use adequate ventilation during application.

Drywall - Joint cement should be sanded smooth, but avoid abrading the paper.

Ferrous Metal - Clean, then prime with Fiberlock IAQ™ 4000 acrylic DTM primer.

Wood - Seal knots and stains with Fiberlock IAQ 5000 stain-blocking primer.

Masonry Block - Apply one coat of Fiberlock IAQ 3000 acrylic block filler if a denser surface is desired.

APPLICATION PROCEDURES FOR AFTERSHOCK™

APPLICATION TOOLS

Apply AfterShock with brush, roller, or airless spray equipment. If using airless spray equipment, AfterShock can be successfully applied with a .017-.019 tip setting.

PRODUCT APPLICATION

Remove gross filth or heavy soil. For heavily soiled areas, a pre-cleaning step is required. Apply AfterShock generously and uniformly by brush, roller or airless spray and ensure that the surface is completely coated. Allow to air dry. Clean and inspect regularly for damage to coating film- reapply if cured coating film becomes damaged. AfterShock will kill residual mold and mildew on the surface, and then will prevent the growth of mold and mildew on the surface of the cured film.

FIRST AID

Have the product label or MSDS with you when calling a poison control center or doctor, or going for treatment.

IF IN EYES: Hold eye open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye. Call a poison control center or doctor for further treatment advice. **IF INHALED:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth, if possible. Call a poison control center or doctor for further treatment advice. **IF SWALLOWED:** Do not induce vomiting unless told to do so by a poison control center or doctor. Do not give any liquid to the person. Do not give anything by mouth to an unconscious person. **IF ON SKIN OR CLOTHING:** Take off contaminated clothing. Rinse skin immediately with plenty of water for 15-20 minutes.

PRECAUTIONS

It is a violation of Federal law to use this product in a manner inconsistent with its labeling. Do not contaminate water, food or feed by storage or disposal.

PESTICIDE STORAGE: Close container after each use. Keep from freezing. **PESTICIDE DISPOSAL:** Wastes resulting from the use of this product may be disposed of on site or at an approved waste disposal facility. **CONTAINER DISPOSAL:** Triple rinse (or equivalent). Then offer for recycling or reconditioning, or puncture and dispose of in a sanitary landfill, or incineration, or, if allowed by state and local authorities, by burning. If burned, stay out of smoke.

CLEAN UP

Clean tools and drippings with warm soapy water before AfterShock dries.

**FOR MEDICAL ASSISTANCE, CALL YOUR LOCAL
POISON CONTROL CENTER or 800-222-1222
PRECAUTIONARY STATEMENTS**

HAZARDOUS TO HUMANS

CAUTION

Harmful if swallowed or inhaled. Avoid breathing spray mist. Avoid contact with skin, eyes, or clothing. Wash thoroughly with soap and water after handling. Remove contaminated clothing before reuse. When applying with a sprayer, applicator should wear a dust/mist filtering respirator (MSHA/NIOSH approval number prefix TC-21C) or a NIOSH approved respirator with any R, P, N, or HE filter.

Do not apply this product in or on electric equipment due to the possibility of shock hazard.

HMIS HAZARD RATING							
Health	1	Flammability	0	Reactivity	0	Personal Protection	E
HAZARD INDEX 0=Minimal, 1=Slight, 2=Moderate, 3=Serious, 4=Severe							
PERSONAL PROTECTION CODE: E= Safety glasses, Gloves, and Protective Clothing for all applications.							

0854

IMPORTANT:

These suggestions and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as conditions and methods of use of this product are beyond our control. Neither Fiberlock Technologies, Inc., nor its agents shall be responsible for the use or results of use of this product or any injury, loss or damage, direct or consequential. We recommend that the prospective user determine the suitability of Aftershock for each specific project and for the health and safety of personnel working in the area.